


2W, Fixed input voltage, isolated & unregulated
positive-negative dual/single output

FEATURES

- DIP package
- Efficiency up to 83%
- Isolation voltage: 6KVDC
- Operating temperature range: -40°C to +105°C
- Continuous short circuit protection
- Internal SMD construction
- International standard pin-out



Patent Protection RoHS

G_D-2W & H_D-2W series is specially designed for applications where the positive and negative input power supply of high isolation is required in a distributed power supply system. It is suitable for:

1. Where the voltage of the input power supply is stable (voltage variation: $\pm 10\%V_{in}$);
 2. Where isolation is necessary between input and output (isolation voltage $\leq 6000VDC$);
 3. Where do not has high requirement of line regulation and the ripple & noise of the output voltage;
- Such as: pure digital circuits, low frequency analog circuits, IGBT-driven circuits, etc.

Selection Guide

Part No.	Input Voltage (VDC)	Output		Efficiency (%.Min./Typ.) @ Full Load	Max. Capacitive Load * (µF)
	Nominal (Range)	Output Voltage (VDC)	Output Current (mA) (Max./Min.)		
G0505D-2W	5 (4.5-5.5)	±5	±200/±20	72/76	100
G0509D-2W		±9	±111/±12	75/79	
G0512D-2W		±12	±84/±9	76/80	
G0515D-2W		±15	±67/±7	77/81	
H0505D-2W		5	400/40	72/76	
H0509D-2W	9	222/23	75/79		
H0512D-2W	12	167/17	76/80		
G1205D-2W	12 (10.8-13.2)	±5	±200/±20	75/79	100
G1209D-2W		±9	±111/±12	77/81	
G1212D-2W		±12	±84/±9	78/82	
G1215D-2W		±15	±67/±7	79/83	
H1205D-2W		5	400/40	74/78	
H1209D-2W	9	222/23	77/81		
H1212D-2W	12	167/17	78/82		
H1215D-2W	15	133/14	79/83		
H1515D-2W	15 (13.5-16.5)	15	133/14	79/83	220
G2409D-2W	24 (21.6-26.4)	±9	±111/±12	78/82	100
H2405D-2W		5	400/40	75/79	220
H2409D-2W		9	222/23	78/82	
H2412D-2W		12	167/17	79/83	

Note: * The capacitive loads of positive and negative outputs are identical.

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Current (no-load/full load)	5V input	—	40/500	—	mA
	12V input	—	15/200	—	
	15V input	—	10/160	—	
	24V input	—	7/98	—	

Surge Voltage (1sec. max.)	5V input	-0.7	--	9	VDC
	12V input	-0.7	--	18	
	15V input	-0.7	--	21	
	24V input	-0.7	--	30	
Reflected Ripple Current	5V input	--	15	--	mA
	Others input	--	5	--	
Input Filter	Capacitor filter				

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit	
Output Voltage Accuracy	See tolerance envelope graph (Fig. 1)					
Line Regulation	Input voltage change: $\pm 1\%$	--	--	± 1.2	--	
Balance of Output Voltage	Dual output, balanced load	--	± 0.5	± 1	%	
Load Regulation	10%-100% load	5VDC output	--	--		20
		9VDC output	--	--		15
		12VDC output	--	--		15
		15VDC output	--	--		15
Ripple & Noise*	20MHz bandwidth	--	150	250	mVp-p	
Temperature Drift Coefficient	100% load	--	--	± 0.03	%/°C	
Output Short Circuit Protection	Continuous, self-recovery					

Notes: 1.Unbalanced load of positive-negative dual output module: $\pm 5\%$.

2.*Ripple and noise tested with "parallel cable" method, please see *DC-DC Converter Application Notes* for specific operation methods.

General Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit	
Isolation Voltage	Input-output, with the test time of 1 minute and the leak current lower than 1mA	6000	--	--	VDC	
Isolation Resistance	Input-output, isolation voltage 500VDC	1000	--	--	M Ω	
Isolation Capacitance	Input-output, 100KHz/0.1V	--	5	--	pF	
Operating Temperature	Derating if the temperature $\geq 85^\circ\text{C}$, (see Fig. 2)	-40	--	105	°C	
Storage Temperature		-55	--	125		
Casing Temperature Rise	Ta=25°C	--	25	--		
Pin Welding Resistance Temperature	Welding spot is 1.5mm away from the casing, 10 seconds	--	--	300		
Storage Humidity	Non-condensing	--	--	95		
Switching Frequency	100% load, nominal input voltage	5VDC input	--	60	--	KHz
		Others input	--	80	--	
MTBF	MIL-HDFK-217F@25°C	3500	--	--	K hours	

Physical Specifications

Casing Material	Black flame-retardant and heat-resistant plastic (UL94-V0)
Package Dimensions	32.30*16.65*10.30mm
Weight	8.2g(Typ.)
Cooling Method	Free air convection

EMC Specifications

EMI	Conducted disturbance	CISPR22/EN55022	CLASS B (see Fig. 5 for recommended circuit)
	Radiated emission	CISPR22/EN55022	CLASS B (see Fig. 5 for recommended circuit)
EMS	Electrostatic discharge	IEC/EN61000-4-2	Contact $\pm 6\text{KV}$ perf. Criteria B

Product Characteristic Curve




Fig. 1






Fig. 2



Design Reference

1. Typical application

If it is required to further reduce input and output ripple, a filter capacitor can be connected to the input and output terminals, see Fig.3. Moreover, choosing suitable filter capacitor is very important, start-up problems may be caused by too large capacitance. To ensure the modules running well, the recommended capacitive load values as shown in Table 1.

The simplest device for output voltage regulation, over-voltage and over-current protection is a linear voltage regulator with overheat protection that is connected to the input or output end in series (see Fig. 4).




Fig.3




Fig.4

Recommended capacitive load value table (Table 1)

Vin (VDC)	Cin (μF)	Single Vout (VDC)	Cout (μF)	Dual Vout (VDC)	Cout (μF)
5	4.7	5	10	±5	4.7
12	2.2	9/12	2.2	±9/±12	1
15	2.2	15	1	±15	0.47
24	1	--	--	--	--

It is not recommended to connect any external capacitor when output power is less than 0.5W.

2. EMC typical recommended circuit (CLASS B)




Fig. 5


Input voltage (V)	5/12/15/24	
EMI	C1, C2	4.7μF /50V
	C3	Refer to the Cout in Fig.3
	LDM	6.8μH

3. Output load requirements

To ensure the module work efficiently and reliably, during the operation, the min. output load should be no less than 10% of the full load. If the actual output power is low, please connect a resistor to the output terminal in parallel, with a recommended resistance which is 10% of the rated power, and derating is required during operation.

4. For more information please find the application notes on www.mornsun-power.com

Dimensions and Recommended Layout



Notes:

1. Packing Information please refer to 'Product Packing Information'. Packing bag number: 58200017;
2. If the product is operated under the min. required load, the product performance cannot be guaranteed to comply with all performance indexes in this datasheet;
3. The max. capacitive load should be tested within the input voltage range and under full load conditions;
4. Unless otherwise specified, data in this datasheet should be tested under the conditions of Ta=25°C, humidity<75% when inputting nominal voltage and outputting rated load;
5. All index testing methods in this datasheet are based on our Company's corporate standards;
6. The performance indexes of the product models listed in this manual are as above, but some indexes of non-standard model products will exceed the above-mentioned requirements, and please directly contact our technicians for specific information;
7. We can provide product customization service;
8. Specifications of this product are subject to changes without prior notice.

MORNSUN Guangzhou Science & Technology Co., Ltd.

Address: No. 5, Kehui St. 1, Kehui Development Center, Science Ave., Guangzhou Science City, Luogang District, Guangzhou, P. R. China
Tel: 86-20-38601850-8801 Fax: 86-20-38601272 E-mail: info@mornsun.cn